



Product Information:

GROUND FORCE 2HSS

SEMI-SYNTHETIC 2-STROKE ENGINE OIL FOR PREMIX & INJECTOR SYSTEMS

Description

Groundforce 2HSS is a top quality synthetic boosted 2-stroke oil, utilising the latest performance additive technology, for protection and performance. Provides maximum film strength and anti-wear characteristics, for prolonging engine life.

Groundforce 2HSS is a low smoke, clean burning lubricant and reduces the need for maintenance on ports and exhausts. Provides all season reliability for modern 2-stroke engines when used in horticultural or plant equipment. This lubricant has been developed to meet the need for a specialised product for horticultural contractors and hired equipment where a certain amount of severe treatment has to be catered for and where adherence to mixtures ratios cannot be guaranteed.

Applications

Groundforce 2HSS has been formulated for use in the engines of all two stroke powered horticultural equipment. This includes mowers, chain saws, chippers, shredders, scarifiers, weed cutters, strimmers and hedge cutters. Can also be used in other air-cooled engines powering abrasive disc cutters, angle grinders and general 2-stroke hire equipment. For premix the mixing process and ratios should be as detailed in the manufacturers handbook. Can also be used via a direct injection system.

Performance Levels

API TC+

JASO FD

ISO-L-EGD

Approved and endorsed by the British Agricultural & General Machinery Association.

Physical Characteristics

Appearance	Red liquid
Density at 15.6 °C	0.863
Kinematic Viscosity @ 100 °C (cSt)	8.9
Kinematic Viscosity @ 40 °C (cSt)	55.3
Viscosity Index	140
Closed Flash Point (°C)	110
Sulphated Ash (%wt)	<0.10

Figures based on average production values.

Part No.s: HSS100, HSS500, HSS001, HSS004, HSS025, HSS205

(TDS Groundforce 2HSS – 210116 Issue 4)

